

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

1 Identification

- **Product identifier**
- **Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural**
- **Product number:** 1286
- **Application of the substance / the mixture** Food flavorings

- **Details of the supplier of the safety data sheet**

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Advanced Biotech makes NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Advanced Biotech product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Advanced Biotech product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Advanced Biotech product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

- **Manufacturer/Supplier:**

Advanced Biotech
 10 Taft Road
 Totowa, NJ 07512 USA

- **Information department:**

Product Safety Department
 productsafety@adv-bio.com

- **Emergency telephone number:**

1(800)535-5053 (Info Trac)
 1(352)323-3500 (International)
 During normal business hours: 1(973)339-6242

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements** Harmful in contact with skin or if inhaled.

- **GHS label elements**

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Continued on page 2)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 1)

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

ethyl acrylate

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H317 May cause an allergic skin reaction.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Continued on page 3)

Safety Data Sheet




acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 2)

· Dangerous components:		
CAS: 105-37-3	ethyl propionate  Flam. Liq. 2, H225	99.0%
CAS: 140-88-5	ethyl acrylate  Flam. Liq. 2, H225;  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	1.0%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
 Supply fresh air and be sure to call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information**
 Cool endangered receptacles with water spray.
 Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.

(Continued on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 3)

- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 105-37-3	ethyl propionate	6.3 ppm
CAS: 140-88-5	ethyl acrylate	8.3 ppm

· **PAC-2:**

CAS: 105-37-3	ethyl propionate	69 ppm
CAS: 140-88-5	ethyl acrylate	36 ppm

· **PAC-3:**

CAS: 105-37-3	ethyl propionate	410 ppm
CAS: 140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
 The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
 At this time, the remaining constituent has no known exposure limits.

(Continued on page 5)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 4)

CAS: 140-88-5 ethyl acrylate

PEL	Long-term value: 100 mg/m ³ , 25 ppm Skin
REL	See Pocket Guide App. A
TLV	Short-term value: 61 mg/m ³ , 15 ppm Long-term value: 20 mg/m ³ , 5 ppm

- **Additional information:** The lists that were valid during the creation were used as a basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

US

(Continued on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 5)

9 Physical and chemical properties

<ul style="list-style-type: none"> · Information on basic physical and chemical properties · General Information · Appearance: <ul style="list-style-type: none"> Form: Liquid Color: According to product specification · Odor: According to product specification · Odor threshold: Not determined. 	
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-74 °C (-101.2 °F)
Boiling point/Boiling range:	99 °C (210.2 °F)
· Flash point:	12 °C (53.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	475 °C (887 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	11 Vol %
· Vapor pressure at 20 °C (68 °F):	36 hPa (27 mm Hg)
· Density at 20 °C (68 °F):	0.893 g/cm ³ (7.45209 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	22 g/l
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
· Other information	No further relevant information available.

US

(Continued on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 6)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	3,386 mg/kg
Dermal	LD50	183,400 mg/kg (rabbit)
Inhalative	LC50/4 h	218,000 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 140-88-5 | ethyl acrylate

2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.

(Continued on page 8)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural



(Continuation of page 7)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------|---|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1195 |
| · UN proper shipping name | |
| · DOT | Ethyl propionate |
| · ADR | 1195 Ethyl propionate |
| · IMDG, IATA | ETHYL PROPIONATE |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| ----- | |
| · ADR | |
| |  |
| · Class | 3 (F1) Flammable liquids |

(Continued on page 9)


Safety Data Sheet
 acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 8)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1195 ETHYL PROPIONATE, 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Continued on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 9)

· Section 313 (Specific toxic chemical listings):

CAS: 140-88-5 | ethyl acrylate

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

CAS: 140-88-5 | ethyl acrylate

WARNING: Consuming this product can expose you to Ethyl Acrylate, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov/food.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

CAS: 140-88-5 | ethyl acrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 140-88-5 | ethyl acrylate

· GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

ethyl acrylate

· Hazard statements

H225 Highly flammable liquid and vapor.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Continued on page 11)

Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

(Continuation of page 10)

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Relevant phrases**

- H225 Highly flammable liquid and vapor.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.

• **Department issuing SDS:** Product Safety Department

• **Contact:**

Product Safety Department
 productsafety@adv-bio.com

• **Date of preparation / last revision** 08/24/2018 / -

• **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

(Continued on page 12)



Safety Data Sheet

acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

Trade name: Ethyl Acrylate 1% in Ethyl Propionate natural

Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Continuation of page 11)