

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

### 1 Identification

- **Product identifier**
- **Trade name: Acetaldehyde 50% in EtOH synthetic**
- **Product number: 2024**
- **CAS Number: 75-07-0 / 64-17-5 (7518-70-9: 1-Ethoxyethanol)**
- **EINECS Number: 200-836-8 / 200-578-6**
- **Application of the substance / the mixture** Food flavorings

- **Details of the supplier of the safety data sheet**

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Advanced Biotech makes NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Advanced Biotech product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Advanced Biotech product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Advanced Biotech product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

- **Manufacturer/Supplier:**

Advanced Biotech  
 10 Taft Road  
 Totowa, NJ 07512 USA

- **Information department:**

Product Safety Department  
 productsafety@adv-bio.com

- **Emergency telephone number:**

1(800)535-5053 (Info Trac)  
 1(352)323-3500 (International)  
 During normal business hours: 1(973)339-6242

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Eye Irrit. 2A H319 Causes serious eye irritation.

(Continued on page 2)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 1)

STOT SE 3 H335 May cause respiratory irritation.

· **Label elements** Harmful in contact with skin or if inhaled.

· **GHS label elements**

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.  
 The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetaldehyde

· **Hazard statements**

- H224 Extremely flammable liquid and vapor.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.

· **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2  
 Fire = 4  
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2  
 FIRE 4 Fire = 4  
 REACTIVITY 0 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Continued on page 3)

**Safety Data Sheet**  
 acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**



· **vPvB:** Not applicable.

(Continuation of page 2)

**3 Composition/information on ingredients**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

|              |  |       |
|--------------|--|-------|
| CAS: 75-07-0 | acetaldehyde<br> | 50.0% |
| CAS: 64-17-5 | ethyl alcohol<br> | 50.0% |

**4 First-aid measures**

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Immediately call a doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**5 Fire-fighting measures**

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture**

Product may disassociate to Acetaldehyde and Ethanol

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

US

(Continued on page 4)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 3)

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
 Dilute with plenty of water.  
 Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.
- **Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

|              |               |           |
|--------------|---------------|-----------|
| CAS: 75-07-0 | acetaldehyde  | 45 ppm    |
| CAS: 64-17-5 | ethyl alcohol | 1,800 ppm |

· **PAC-2:**

|              |               |           |
|--------------|---------------|-----------|
| CAS: 75-07-0 | acetaldehyde  | 270 ppm   |
| CAS: 64-17-5 | ethyl alcohol | 3300* ppm |

· **PAC-3:**

|              |               |            |
|--------------|---------------|------------|
| CAS: 75-07-0 | acetaldehyde  | 840 ppm    |
| CAS: 64-17-5 | ethyl alcohol | 15000* ppm |

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep receptacle tightly sealed.  
 Do not gas tight seal receptacle.

(Continued on page 5)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 4)

Store in cool, dry conditions in well sealed receptacles.  
 Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

**CAS: 75-07-0 acetaldehyde**

|     |  |
|-----|--|
| PEL | Long-term value: 360 mg/m <sup>3</sup> , 200 ppm   |
| REL | See Pocket Guide Apps. A and C                     |
| TLV | Ceiling limit value: 45 mg/m <sup>3</sup> , 25 ppm |

**CAS: 64-17-5 ethyl alcohol**

|     |   |
|-----|---|
| PEL | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm  |
| REL | Long-term value: 1900 mg/m <sup>3</sup> , 1000 ppm  |
| TLV | Short-term value: 1880 mg/m <sup>3</sup> , 1000 ppm |

- **Additional information:** The lists that were valid during the creation were used as a basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.  
 Avoid contact with the eyes.  
 Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Continued on page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 5)

- **Penetration time of glove material**  
 The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

|                 |                                    |
|-----------------|------------------------------------|
| Form:           | Liquid                             |
| Color:          | According to product specification |
| Odor:           | According to product specification |
| Odor threshold: | Not determined.                    |

· **pH-value at 20 °C (68 °F):** 5

· **Change in condition**

|                              |               |
|------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 35 °C (95 °F) |

· **Flash point:** -3 °C (26.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 140 °C (284 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

|        |           |
|--------|-----------|
| Lower: | 3.5 Vol % |
| Upper: | 57 Vol %  |

· **Vapor pressure at 20 °C (68 °F):** 1 hPa (0.8 mm Hg)

· **Density at 20 °C (68 °F):** 0.873 g/cm<sup>3</sup> (7.28519 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

**Water:** Fully miscible.

(Continued on page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 6)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 50.0 %
  - VOC content:** 50.00 %
  - 436.5 g/l / 3.64 lb/gal
- **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
 No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
 No dangerous decomposition products known.  
 Product may disassociate to Acetaldehyde and Ethanol.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

**ATE (Acute Toxicity Estimate)**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 1,322 mg/kg (rat) |
| Inhalative | LC50/4 h | 74 mg/l (rat)     |

**CAS: 75-07-0 acetaldehyde**

|            |          |                 |
|------------|----------|-----------------|
| Oral       | LD50     | 661 mg/kg (rat) |
| Inhalative | LC50/4 h | 37 mg/l (rat)   |

**CAS: 64-17-5 ethyl alcohol**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 7,060 mg/kg (rat) |
| Inhalative | LC50/4 h | 20,000 mg/l (rat) |

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

(Continued on page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 7)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- Harmful
- Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

|              |               |    |
|--------------|---------------|----|
| CAS: 75-07-0 | acetaldehyde  | 2B |
| CAS: 64-17-5 | ethyl alcohol | 1  |

· **NTP (National Toxicology Program)**

|              |              |   |
|--------------|--------------|---|
| CAS: 75-07-0 | acetaldehyde | R |
|--------------|--------------|---|

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

US

(Continued on page 9)



## Safety Data Sheet

acc. to OSHA HCS




Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 8)

### 14 Transport information

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· UN-Number</li> <li>· DOT, ADR, IMDG, IATA</li> </ul>   | <p>UN1993</p>  |
| <ul style="list-style-type: none"> <li>· UN proper shipping name</li> <li>· DOT</li> <li>· ADR</li> <li>· IMDG</li> <li>· IATA</li> </ul> | <p>Flammable liquids, n.o.s. (Acetaldehyde, Ethanol)<br/>         1993 Flammable liquids, n.o.s. (Acetaldehyde, Ethanol)<br/>         FLAMMABLE LIQUID, N.O.S. (ACETALDEHYDE, ETHANOL (ETHYL ALCOHOL))<br/>         FLAMMABLE LIQUID, N.O.S. (ACETALDEHYDE, ETHANOL)</p> |
| <ul style="list-style-type: none"> <li>· Transport hazard class(es)</li> <li>· DOT</li> </ul>   | <div style="text-align: center;">  </div> <p>3 Flammable liquids</p>   |
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>  | <p>3<br/>3</p>   |
| <ul style="list-style-type: none"> <li>· ADR</li> </ul>   | <div style="text-align: center;">  </div>   |
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>  | <p>3 (F1) Flammable liquids<br/>3</p>  |
| <ul style="list-style-type: none"> <li>· IMDG, IATA</li> </ul>  | <div style="text-align: center;">  </div>   |
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>  | <p>3 Flammable liquids<br/>3</p>   |
| <ul style="list-style-type: none"> <li>· Packing group</li> <li>· DOT, ADR, IMDG, IATA</li> </ul>   | <p>I</p>   |
| <ul style="list-style-type: none"> <li>· Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>                                   | <p>No</p>  |
| <ul style="list-style-type: none"> <li>· Special precautions for user</li> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> </ul>  | <p>Warning: Flammable liquids<br/>33<br/>F-E,S-E</p>   |

(Continued on page 10)

**Safety Data Sheet**  
 acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 9)

|  |   |
|--|---|
| · <b>Stowage Category</b>  | E   |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.   |
| · <b>Transport/Additional information:</b>                                       |   |
| · <b>DOT</b>   |   |
| · <b>Quantity limitations</b>  | On passenger aircraft/rail: Forbidden<br>On cargo aircraft only: 30 L   |
| · <b>ADR</b>   |   |
| · <b>Excepted quantities (EQ)</b>  | Code: E3<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 300 ml |
| · <b>IMDG</b>  |   |
| · <b>Limited quantities (LQ)</b>   | 0   |
| · <b>Excepted quantities (EQ)</b>  | Code: E3<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 300 ml |
| · <b>UN "Model Regulation":</b>  | UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ACETALDEHYDE, ETHANOL), 3, I   |

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

This product contains the following EPCRA section 313 chemicals subject to the Reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40 CFR 372):  
 Acetaldehyde CAS 75-07-00

CAS: 75-07-0 | acetaldehyde

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

CAS: 75-07-0 | acetaldehyde

**WARNING:** Consuming this product can expose you to Acetaldehyde, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov/food](http://www.P65Warnings.ca.gov/food).

Acetaldehyde CAS-no. 75-07-0 (50% by weight)

(Continued on page 11)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 10)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 64-17-5 ethyl alcohol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 75-07-0 acetaldehyde

B2

· **TLV (Threshold Limit Value established by ACGIH)**

CAS: 75-07-0 acetaldehyde

A3

CAS: 64-17-5 ethyl alcohol

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

CAS: 75-07-0 acetaldehyde

· **GHS label elements**

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetaldehyde

· **Hazard statements**

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

(Continued on page 12)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2018

Reviewed on 05/16/2018

**Trade name: Acetaldehyde 50% in EtOH synthetic**

(Continuation of page 11)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H224 Extremely flammable liquid and vapor.
- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.

· **Department issuing SDS:** Product Safety Department

· **Contact:**

Product Safety Department  
 productsafety@adv-bio.com

· **Date of preparation / last revision** 08/24/2018 / -

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Liq. 1: Flammable liquids – Category 1
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 4: Acute toxicity – Category 4
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Carc. 2: Carcinogenicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3