

Printing date 01/16/2024 Reviewed on 01/16/2024

1 Identification

· Product identifier

· Trade name: Trans-2-Hexenol 50% Ethanol natural

· Product number: 1412

• CAS Number: 928-95-0/64-17-5 • EINECS Number: 213-19-12/200-578-6

· Application of the substance / the mixture Flavoring Ingredients

Details of the supplier of the safety data sheet

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Advanced Biotech makes NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Advanced Biotech product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Advanced Biotech product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Advanced Biotech product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

· Manufacturer/Supplier:

Advanced Biotech 10 Taft Road Totowa, NJ 07512 USA

· Information department:

Product Safety Department productsafety@adv-bio.com

Emergency telephone number:

Infotrac: 1-800-535-5053 (Domestic) & 1-352-323-3500 (International)

Email: responders@infotrac.net & During normal business hours: 1-973-339-6242

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Continued on page 2)

(Continuation of page 1)



Safety Data Sheet acc. to OSHA HCS (29 CFR § 1910.1200)

Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

trans-2-Hexenol

· Hazard statements

H225 Highly flammable liquid and vapor.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe/dust/fume/gas/mist/vapors/spray.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

Store locked up. P405

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Other hazards

Health = *3 Fire = 3

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

(Continued on page 3)



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

	(Continuation	on of page 2)
· Dangerous compon	nents:	
0, 10. 0 1 11	Ethanol Tritation 2A, H319 Ethanol Ethanol	25-50%
CAS: 928-95-0	trans-2-Hexenol Flammable Liquids 3, H226; Skin Corrosion 1B, H314; Eye Damage 1, H318; Sensitization - Skin 1B, H317	25-50%

4 First-aid measures

- · Description of first aid measures
- · **General information:** Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and be sure to call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

(Continued on page 4)



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

(Continuation of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Ac	tion Criteria for Chemicals	
· PAC-1:		
CAS: 64-17-5	Ethanol	1,800 ppm
PAC-2:		
CAS: 64-17-5	Ethanol	3300* ppm
· PAC-3:		
CAS: 64-17-5	Ethanol	15000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS	CAS: 64-17-5 Ethanol		
PEL	Long-term value: 1900 mg/m³, 1000 ppm		
REL	Long-term value: 1900 mg/m³, 1000 ppm		
TLV	Short-term value: 1000 ppm		
	A3		

- Additional information: The lists that were valid during the creation were used as a basis.
- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Continued on page 5)



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

(Continuation of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: According to product specification

Odor: According to product specification

· Odor threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

· Flammability (solid, gaseous):

Melting point/Melting range:
Boiling point/Boiling range:Undetermined.
158 °C (316.4 °F)Flash point:13 °C (55.4 °F)

Highly flammable.

· Auto igniting: 425 °C (797 °F)

(Continued on page 6)



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

	(Continuation of page	
Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.	
Explosion limits:		
Lower:	3.5 Vol %	
Upper:	15 Vol %	
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)	
Density at 20 °C (68 °F):	0.849 g/cm³ (7.08491 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:	()"	
Organic solvents:	50.0 %	
VOC content:	50.00 %	
	424.5 g/l / 3.54 lb/gal	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	· LD/LC50 values that are relevant for classification:		
	CAS: 64-1	7-5 Ethan	ol
j	Oral	LD50	7,060 mg/kg (rat)
	Inhalative	LC50/4 h	20,000 mg/l (rat)

(Continued on page 7)

1



Safety Data Sheet acc. to OSHA HCS (29 CFR § 1910.1200)

Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

			(Continuation of page 6)
CAS: 928	-95-0 tran	s-2-Hexenol	
Oral	LD50	3,500 mg/kg (ATE)	
		3,500 mg/kg (rat)	
Dermal	LD50	4,500 mg/kg (ATE)	
		4,500 mg/kg (rabbit)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

İrritant

· Carcinogenic categories

· IARC (International Agency for Research on Ca	incer)
CAS: 64-17-5 Ethanol	6/1

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Continued on page 8)



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

(Continuation of page 7)

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG	Flammable liquids, n.o.s. (Ethanol, trans-2-Hexenol) FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETH' ALCOHOL), trans-2-Hexenol) FLAMMABLE LIQUID, N.O.S. (ETHANOL, trans-
	Hexenol)
Transport hazard class(es)	
DOT	
P AMMAR F LIGHT	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-E
Stowage Category	B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

(Continuation of page 8)

· IMDG

· Limited quantities (LQ)

Excepted quantities (EQ)

1L Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation": UN 1993 FLAMMABLE LIQUID. N.O.S. (ETHANOL

(ETHYL ALCOHOL), TRANS-2-HEXENOL), 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 64-17-5 Ethanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 64-17-5 Ethanol А3

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Continued on page 10)

(Continuation of page 9)



Safety Data Sheet acc. to OSHA HCS (29 CFR § 1910.1200)

Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

· Hazard pictograms





GHS02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

trans-2-Hexenol

· Hazard statements

H225 Highly flammable liquid and vapor.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe/dust/fume/gas/mist/vapors/spray.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

· Department issuing SDS: Product Safety Department

· Contact:

Product Safety Department productsafety@adv-bio.com

· Date of preparation / last revision 01/16/2024

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Continued on page 11)



Printing date 01/16/2024 Reviewed on 01/16/2024

Trade name: Trans-2-Hexenol 50% Ethanol natural

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2
Flammable Liquids 3: Flammable liquids – Category 3
Skin Corrosion 1B: Skin corrosion/irritation – Category 1B
Eye Damage 1: Serious eye damage/eye irritation – Category 1
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1 Sensitization - Skin 1B: Skin sensitisation - Category 1B (Continuation of page 10)

·US