

Printing date 01/16/2024 Reviewed on 12/05/2023

1 Identification

· Product identifier

· Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

· Product number: 2073

• CAS Number: 75-07-0 / 120-51-4 • EINECS Number: 200-836-8 / 204-402-9

· Application of the substance / the mixture Flavoring Ingredients

Details of the supplier of the safety data sheet

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Advanced Biotech makes NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Advanced Biotech product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Advanced Biotech product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Advanced Biotech product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

· Manufacturer/Supplier:

Advanced Biotech 10 Taft Road Totowa, NJ 07512 USA

· Information department:

Product Safety Department productsafety@adv-bio.com

· Emergency telephone number:

Infotrac: 1-800-535-5053 (Domestic) & 1-352-323-3500 (International)

Email: responders@infotrac.net & During normal business hours: 1-973-339-6242

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 1 H224 Extremely flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 2 H341 Suspected of causing genetic defects.

Carcinogenicity 1B H350 May cause cancer.



Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

(Continued on page 2)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 1)

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetaldehyde

Benzyl benzoate

· Hazard statements

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 4 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 4

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

(Continued on page 3)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

	(Contin	uation of page 2)	
· Dangerous components:			
CAS: 75-07-0 EINECS: 200-836-8	Acetaldehyde Flammable Liquids 1, H224; Germ Cell Mutagenicity 2, H341; Carcinogenicity 1B, H350; Acute Toxicity - Oral 4, H302; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	≥25-≤100%	
CAS: 120-51-4 EINECS: 204-402-9	Benzyl benzoate Oral 4, H302	≥25-≤100%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air: consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Continued on page 4)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 75-07-0 Acetaldehyde	45 ppm	
CAS: 120-51-4 Benzyl benzoate	5.7 mg/m³	
· PAC-2:		
CAS: 75-07-0 Acetaldehyde	270 ppm	
CAS: 120-51-4 Benzyl benzoate	63 mg/m³	
· PAC-3:		
CAS: 75-07-0 Acetaldehyde	840 ppm	
CAS: 120-51-4 Benzyl benzoate	380 mg/m³	

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS	: 75-07-0 Acetaldehyde
PEL	Long-term value: 360 mg/m³, 200 ppm

(Continued on page 5)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 4)

REL See Pocket Guide Apps. A and C

TLV Ceiling limit value: 25 ppm

Α2

- · Additional information: The lists that were valid during the creation were used as a basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liqui

Color: According to product specification
Odor: According to product specification

(Continued on page 6)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

	(Continuation of page 5
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 21 °C (69.8 °F)
· Flash point:	5 °C (41 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto igniting:	140 °C (284 °F)
Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	4 Vol % 57 Vol %
· Vapor pressure at 20 °C (68 °F):	1 hPa (0.8 mm Hg)
 Density: Relative density Vapor density Evaporation rate 	Not determined. Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content: Organic solvents: VOC content:	47-53 % 47-53 % 530.0 g/l / 4.42 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Continued on page 7)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values tha	it are relevant for classi	fication:
ATE (Acu	te Toxicity	/ Estimate)	* /
Oral	LD50	794-896 mg/kg	
CAS: 75-0	07-0 Aceta	ldehyde	
Oral	LD50	700 mg/kg (ATE)	
		661 mg/kg (rat)	
Dermal	LD50	3,540 mg/kg (ATE)	
Inhalative	LC50/4 h	37 mg/l (rat)	
CAS: 120	-51-4 Benz	zyl benzoate	6/7
Oral	LD50	1,160 mg/kg (ATE)	
		1,700 mg/kg (rat)	
Dermal	LD50	4,000 mg/kg (ATE)	
		4,000 mg/kg (rabbit)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 75-07-0 Acetaldehyde	2B	
· NTP (National Toxicology Program)		
CAS: 75-07-0 Acetaldehyde	R	
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Continued on page 8)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1089

- · UN proper shipping name
- · DOT

Acetaldehyde · IMDG

· IATA

ACETALDEHYDE, MARINE POLLUTANT

ACETALDEHYDE

- · Transport hazard class(es)
- · DOT



· Class

3 Flammable liquids

· Label

· IMDG





Class

3 Flammable liquids

(Continued on page 9)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

	(Continuation of page
Label	3
·IATA	
· Class	3 Flammable liquids
Label	3
· Packing group · DOT, IMDG, IATA	
Environmental hazards:	Product contains environmentally hazardous substances: Benzyl benzoate
Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code): EMS Number:	33 F-E,S-D
Stowage Category	F-E,3-D
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	0
Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: 30 L
·IMDG	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E3 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 300 ml
UN "Model Regulation":	UN 1089 ACETALDEHYDE, 3, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

CAS: 75-07-0 Acetaldehyde

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

(Continued on page 10)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 9)

· Hazardous Air Pollutants

CAS: 75-07-0 Acetaldehyde

Proposition 65

· Chemicals known to cause cancer:

CAS: 75-07-0 Acetaldehyde

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 75-07-0 Acetaldehyde

B2

· TLV (Threshold Limit Value)

CAS: 75-07-0 Acetaldehyde

A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 75-07-0 Acetaldehyde

GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

Signal word Danger

· Hazard-determining components of labeling:

Acetaldehyde

Benzyl benzoate

· Hazard statements

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment. P241

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Continued on page 11)



Printing date 01/16/2024 Reviewed on 12/05/2023

Trade name: Acetaldehyde 50% in Benzyl Benzoate Synthetic

(Continuation of page 10)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

· Department issuing SDS: Product Safety Department

· Contact:

Product Safety Department productsafety@adv-bio.com

Date of preparation / last revision 01/16/2024

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 1: Flammable liquids – Category 1

Acute Toxicity - Oral 4: Acute toxicity - Category 4
Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Germ Cell Mutagenicity 2: Germ cell mutagenicity - Category 2

Carcinogenicity 1B: Carcinogenicity - Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3