

Date of issue: 01/25/2025

Reviewed on 01/25/2025





Date of issue: 01/25/2025

Reviewed on 01/25/2025

Trade name: Butyl Mercaptan synthetic (Continuation of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labeling: 1-Butanethiol Hazard statements H225 Highly flammable liquid and vapor. H302+H332 Harmful if swallowed or if inhaled. H319 Causes serious eye irritation. Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210 No smoking. P241 Use explosion-proof [electrical/ventilating/lighting] equipment. P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. · Information pertaining to particular dangers for man and environment: Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 4Reactivity = 0 · HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 2FIRE 4 Fire = 4Reactivity = 0 REACTIVITY 0 · Other hazards Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. Classification according to (d)(1)(ii) of § 1910.1200 The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products. · Hazards not otherwise classified There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

(Continued on page 3)

US



Date of issue: 01/25/2025

Reviewed on 01/25/2025

Trade name: Butyl Mercaptan synthetic

(Continuation of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

CAS: 109-79-5 1-Butanethiol Identification number(s)

• EC number: 203-705-3

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Immediately call a doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment: Mouth respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

(Continued on page 4)

s –



Date of issue: 01/25/2025

Reviewed on 01/25/2025

(Continuation of page 3)

Trade name: Butyl Mercaptan synthetic

· Protective Action Criteria for Chemicals

· PAC-1:

4.5 ppm

· PAC-2:

50 ppm

PAC-3:

FAC-J.

2,500 ppm

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

• Components with limit values that require monitoring at the workplace:

CAS: 109-79-5 1-Butanethiol

PEL Long-term value: 35 mg/m³, 10 ppm

REL Ceiling limit value: 1.8* mg/m³, 0.5* ppm *15-min

TLV Long-term value: 0.5 ppm

• Additional information: The lists that were valid during the creation were used as a basis.

• Exposure controls

- Appropriate engineering controls No further data; see section 7.
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.

(Continued on page 5)



Date of issue: 01/25/2025

Trade name: Butyl Mercaptan synthetic

Avoid contact with the eyes and skin.

(Continuation of page 4)

· Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. Penetration time of glove material The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed. Eye protection: Tightly sealed goggles 9 Physical and chemical properties Information on basic physical and chemical properties · General Information Molecular Weight: 90.19 g/mol · Physical state Liquid · Color: According to product specification · Odor: According to product specification Not determined. · Odor threshold: · Melting point/Melting range: -115.7 °C (-176.3 °F) 97 °C (206.6 °F) · Boiling point/Boiling range: · Flammability: Highly flammable. • Explosion limits: · Lower: Not determined. · Upper: Not determined. 13 °C (55.4 °F) · Flash point: · Decomposition temperature: Not determined. · pH-value: Not determined. · Viscosity: · Kinematic: Not determined. · Dynamic: Not determined. Solubility in / Miscibility with · Water: Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not determined. (Continued on page 6)



Date of issue: 01/25/2025

Reviewed on 01/25/2025

Trade name: Butyl Mercaptan synthetic

	(Continuation of page	ə 5)
· Vapor pressure at 20 °C (68 °F):	40 hPa (30 mm Hg)	
Vapor pressure:		
Density at 20 °C (68 °F):	0.843 g/cm³ (7.03484 lbs/gal)	
Relative density	Not determined.	
Refractive Index		
· Vapor density	Not determined.	
Particle characteristics	Not applicable.	
• Other information		
Appearance:		
Form:	Liquid	
Important information on protection of and environment, and on safety.	of health	
Ignition temperature:	Not determined.	
Danger of explosion:	Product is not explosive. However, formation explosive air/vapor mixtures are possible.	of
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	843.0 g/l / 7.04 lb/gal	
Change in condition	3	
Evaporation rate	Not determined.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

 Oral
 LD50
 1,500 mg/kg (ATE)

 Inhalative
 LC50/4 h
 15 mg/l (ATE)

CAS: 109-79-5 1-Butanethiol

and the second s		
Oral	LD50	1,500 mg/kg (ATE)
		1,500 mg/kg (rat)

Inhalative	LC50/4 h	15 mg/l (ATE)
------------	----------	---------------

4,020 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

(Continued on page 7)

⁻ US



Date of issue: 01/25/2025

Reviewed on 01/25/2025

(Continuation of page 6)

Trade name: Butyl Mercaptan synthetic

- · on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
- · Interactive effects No interactive effects between components are known.
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

• OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Assessment by list): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, IMDG, IATA	UN2347	
· UN proper shipping name		
DOT	Butyl mercaptan	
		(Continued on page 8)



Date of issue: 01/25/2025

Reviewed on 01/25/2025

Trade name: Butyl Mercaptan synthetic (Continuation of page 7) · IMDG, IATA **BUTYL MERCAPTAN** Transport hazard class(es) · DOT **3** Flammable liquids Class · Label 3 · IMDG, IATA **3 Flammable liquids** · Class · Label 3 Packing group DOT, IMDG, IATA II. · Environmental hazards: · Marine pollutant: No · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L ·IMDG · Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-D Stowage Category В Segregation Code SG35 Stow "separated from" SGG1-acids SG50 Segregation from foodstuffs as in 7.3.4.2.1, 7.6.3.1.2 or 7.7.3.6. SG57 Stow "separated from" odour-absorbing cargoes · UN "Model Regulation": UN 2347 BUTYL MERCAPTAN, 3, II

(Continued on page 9)



Date of issue: 01/25/2025

Reviewed on 01/25/2025

Trade name: Butyl Mercaptan synthetic

(Continuation of page 8)

15 Regulatory information · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara · Section 355 (extremely hazardous substances): Substance is not listed. Section 313 (Specific toxic chemical listings): Substance is not listed. · TSCA (Toxic Substances Control Act): ACTIVE · Hazardous Air Pollutants Substance is not listed. · Proposition 65 · Chemicals known to cause cancer: Substance is not listed. Chemicals known to cause reproductive toxicity for females: Substance is not listed. · Chemicals known to cause reproductive toxicity for males: Substance is not listed. Chemicals known to cause developmental toxicity: Substance is not listed. Carcinogenic categories · EPA (Environmental Protection Agency) Substance is not listed. · TLV (Threshold Limit Value) Substance is not listed. · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed. GHS label elements Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible. The substance is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labeling: 1-Butanethiol · Hazard statements

H225 Highly flammable liquid and vapor. H302+H332 Harmful if swallowed or if inhaled.

(Continued on page 10)



Date of issue: 01/25/2025

Reviewed on 01/25/2025

Trade name: Butyl Mercaptan synthetic

(C	ontinuation	of	page 9)
	onunuuuon	01	puge o	/

H319 Caus	ses serious eye irritation.	
 Precautionary st 	atements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.	
P303+P361+P353	3 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P305+P351+P338	8 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product Safety Department

· Contact:

Product Safety Department

productsafety@adv-bio.com

- Date of previous version 01/10/2023
- Date of preparation 01/25/2025
- · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit REL: Recommended Exposure Limit
- Flammable liquids 2: Flammable liquids Category 2
- Acute toxicity oral 4: Acute toxicity Category 4
- Eye irritation 2A: Serious eye damage/eye irritation Category 2A