

Printing date 01/16/2024 Reviewed on 01/10/2023

1 Identification

· Product identifier

· Trade name: Butyl Mercaptan synthetic

· Product number: 4080

• CAS Number: 109-79-5 • EC number:

203-705-3
• Application of the substance / the mixture Flavoring Ingredients

Details of the supplier of the safety data sheet

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Advanced Biotech makes NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Advanced Biotech product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Advanced Biotech product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Advanced Biotech product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Manufacturer/Supplier:

Advanced Biotech 10 Taft Road Totowa, NJ 07512 USA

· Information department:

Product Safety Department productsafety@adv-bio.com

· Emergency telephone number:

Infotrac: 1-800-535-5053 (Domestic) & 1-352-323-3500 (International)

Email: responders@infotrac.net & During normal business hours: 1-973-339-6242

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



Acute Toxicity - Oral 4 H302 Harmful if swallowed. Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.

Eye Irritation 2A H319 Causes serious eye irritation.

GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Continued on page 2)

(Continuation of page 1)



Safety Data Sheet acc. to OSHA HCS (29 CFR § 1910.1200)

Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

· Hazard pictograms



GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

1-Butanethiol

· Hazard statements

H225 Highly flammable liquid and vapor. H302+H332 Harmful if swallowed or if inhaled. H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 4 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 4 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Substances

· CAS No. Description

CAS: 109-79-5 1-Butanethiol Identification number(s) EC number: 203-705-3

- US



Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

(Continuation of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

4.5 ppm

(Continued on page 4)



Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic		
	(Continuation of page 3)	
· PAC-2:		
50 ppm		
PAC-3:		
2,500 ppm		

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Com	· Components with limit values that require monitoring at the workplace:				
CAS	CAS: 109-79-5 1-Butanethiol				
	Long-term value: 35 mg/m³, 10 ppm				
REL	Ceiling limit value: 1.8* mg/m³, 0.5* ppm				
	*15-min				
TLV	Long-term value: 0.5 ppm				

- · **Additional information:** The lists that were valid during the creation were used as a basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Continued on page 5)

(Continuation of page 4)



Safety Data Sheet acc. to OSHA HCS (29 CFR § 1910.1200)

Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material should be based on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and cl			
General Information	Molecular Weight: 90.19 g/mol		
· Appearance: Form:	Liquid		
Color:	Liquid According to product specification		
· Odor:	According to product specification		
· Odor threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range:	-115.7 °C (-176.3 °F)		
Boiling point/Boiling range:	97 °C (206.6 °F)		
· Flash point:	13 °C (55.4 °F)		
· Flammability (solid, gaseous):	Highly flammable.		
· Decomposition temperature:	Not determined.		
· Ignition temperature:	Not determined.		
· Danger of explosion:	Product is not explosive. However, formation of explosive air/		
	vapor mixtures are possible.		
· Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
· Vapor pressure at 20 °C (68 °F):	40 hPa (30 mm Hg)		

(Continued on page 6)



Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

(Continuation of page 5)

• **Density at 20 °C (68 °F):** 0.843 g/cm³ (7.03484 lbs/gal)

Relative densityVapor densityEvaporation rateNot determined.Not determined.Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:Not determined.Kinematic:Not determined.Organic solvents:100.0 %VOC content:100.00 %

843.0 g/l / 7.04 lb/gal

· Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	· LD/LC50 values that are relevant for classification:				
Ī	ATE (Acute Toxicity Estimate)				
Ī	Oral	LD50	1,500 mg/kg (ATE)		
	Inhalative	LC50/4 h	15 mg/l (ATE)		

CAS: 109-79-5 1-Butanethiol				
Oral	LD50	1,500 mg/kg (ATE)		
		1,500 mg/kg (rat)		
Inhalative	LC50/4 h	15 mg/l (ATE)		
		4,020 mg/l (rat)		

- Primary irritant effect:
- · on the skin: No irritant effect. · on the eve: Irritating effect.
- Sensitization: No sensitizing effects known.

(Continued on page 7)



Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

· Additional toxicological information:

(Continuation of page 6)

Carcinogenic categories

IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Assessment by list): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, IMDG, IATA UN2347

· UN proper shipping name

DOTButyl mercaptanIMDG, IATABUTYL MERCAPTAN

(Continued on page 8)



Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

(Continuation of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

· Label 3

· IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

· DOT, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Hazard identification number (Kemler code): 33

· EMS Number: F-E,S-D

· Stowage Category B

• Segregation Code SG35 Stow "separated from" SGG1-acids

SG50 Segregation from foodstuffs as in 7.3.4.2.1,

7.6.3.1.2 or 7.7.3.6.

SG57 Stow "separated from" odour-absorbing cargoes

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations** On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 2347 BUTYL MERCAPTAN, 3, II

US



Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

(Continuation of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- Section 355 (extremely hazardous substances):

Substance is not listed.

Section 313 (Specific toxic chemical listings):

Substance is not listed.

TSCA (Toxic Substances Control Act):

ACTIVE

· Hazardous Air Pollutants

Substance is not listed.

Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

Pictograms on label shall be in the shape of a square set at a point and shall include a black hazard symbol on a white background with a red frame sufficiently wide to be clearly visible.

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:
- 1-Butanethiol
- · Hazard statements

H225 Highly flammable liquid and vapor.

H302+H332 Harmful if swallowed or if inhaled.

(Continuation of page 9)



Safety Data Sheet acc. to OSHA HCS (29 CFR § 1910.1200)

Printing date 01/16/2024 Reviewed on 01/10/2023

Trade name: Butyl Mercaptan synthetic

H319 Causes serious eye irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product Safety Department

· Contact:

Product Safety Department productsafety@adv-bio.com

Date of preparation / last revision 01/16/2024

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Oral 4: Acute toxicity - Category 4

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

US